

Charging Cart 32 Slots



Capacity	32 (2 shelves, 16 bays per shelf)	Working temperature	0 °C~30 °C
Supported devices	Mobile devices up to 16"	Working RH%	10%~90%
Charging type	Smart Cycling Charge	Storage temperature	-40 °C~60 °C
Power specification	AC IN: 220~240 V, 50/60 Hz, 8 A Power strip: 220~240 V, 50/60 Hz, 8 A	Storage RH%	5%~95%
		Cart dimensions (W x D x H)	639.6 x 632 x 1039 mm (25.18" x 24.88" x 40.91")
Security	Front door: 2-point steel locking mechanism Rear door: 2-point steel locking mechanism (2 keys included)	Slot dimensions (W x D x H)	Upper side drawer: 26 x 395 x 300.8 mm (1.02" x 15.55" x 11.84")
Casters	Four 5" casters (2 lockable and 2 directional)		Lower side drawer: 26 x 395 x 341.5 mm (1.02" x 15.55" x 13.44")
Door hinge	180°	Weight without devices	54 kg (119.05 lbs)
Work platform loading	20 kg (44.09 lbs)	Power socket	GP.OFG11.005: Type-F (EU)
Shelf loading(ea.)	43.54 kg (95.98 lbs)		GP.OFG11.006: Type-L (IT)
Adapter shelves loading(ea.)	3 kg (6.6 lbs)		GP.OFG11.009: Type-J (CH) GP.OFG11.00B: Type-G (UK)